

PRODUCT SPECIFICATION

White Removable

Description

- White, high bulk, woodfree, filled, uncoated 70gsm.
- Excellent whiteness, opacity and smoothness for its paper type.
- Removable grade: acrylic aqueous adhesive.
- Minimum application temperature: -20°C
- Temperature range: -40°C to +50°C

A general purpose removable adhesive designed for safe use in hot fusing laser and copier printing. Removable adhesive can be used as a deep freeze grade providing the labels are applied at room temperature to dry goods. Please be aware that under some conditions removable adhesives can turn permanent. Always test if unsure. Approved for indirect food contact. The adhesive conforms to the EN71-3 (Toy Safety) & Packaging (Essential Requirements) Regulations. No heavy metals are used in the manufacturing process and typical contents are less than 1 ppm.

Laminate Information

Thickness: 170 mic Weight: 160 gsm

Backing

White high density kraft paper with excellent lay flat properties

Printing Compatability

DRY TONER	LITHO PRINT	InkJet PRINT	LASER PRINT
PCL Digital Office A3 SRA3 SRA3+	PCL A4+ Digital Office A3 SRA3 SRA3+	PCL Digital Office A3 SRA3 SRA3+	PCL Digital Office A3 SRA3 SRA3+

For detailed printing information please refer to our 'Printing Guidelines'

PCL
by
AVERY